Helicopter Satellite Communication (SATCOM): Development of Low-Cost Real-1'ime Voice and Data System for Aeronautical Mobile Satellite Service (AMSS)*

Kcyvan Farazian, Dariush Divsalar, Nasser Golshan, T.K. Wu, Sami Hinedi

Jet Propulsion laboratory California Institute of Technology Mail Stop 238-343 4800 Oak Grove Drive Pasadena, California 91109-8099

January 1993

Abstract

Current helicopter communications are handled by VI 111 radio which is limited in coverage and operational range. '1'here is a real need for helicopter SATCOM system to extend the coverage while meeting the unique conditions imposed by the helicopter operational environment. Exist ing fixed wing aircraft SATCOM systems have been conside reel but do not support helicopter specific requirements, including low cost, size, and weight. Furthermore, the helicopter's wide angle rapid flight maneuvers impose various restrictions on the antenna requirements for continuous coverage. In this paper, various diversity techniques have been investigated for optimum real-time voice and data processing. Coding, modulation, and interleaving are all employed to mitigate periodic signal blockage, due to the main rotor blades, and high Doppler frequency shifts. Also, potential 10w-cost omni-directional antenna designs and locations on the helicopter are presented.

For questions please contact:

Keyvan II. Farazian FAA 1 Ielicopter Satellite Communication Project Tel. (818) 354-4630 Fax (818) 3S4-6825

^{*} This work was carried out by the Jet 1'repulsion Laboratory, California Institute of Technology, Pasadena, CA, and was sponsored by the United States Federal Aviation Administration (FAA) through an agreement with the National Aeronautics and Spare Administration.